



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/669,371	09/25/2003	In Duk Song	2658-0305P	3363

2292 7590 03/03/2009
BIRCH STEWART KOLASCH & BIRCH
PO BOX 747
FALLS CHURCH, VA 22040-0747

EXAMINER

NGUYEN, LAUREN

ART UNIT	PAPER NUMBER
----------	--------------

2871

NOTIFICATION DATE	DELIVERY MODE
-------------------	---------------

03/03/2009

ELECTRONIC

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Notice of the Office communication was sent electronically on above-indicated "Notification Date" to the following e-mail address(es):

mailroom@bskb.com

Office Action Summary	Application No. 10/669,371	Applicant(s) SONG, IN DUK	
	Examiner LAUREN NGUYEN	Art Unit 2871	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 1/15/2009.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-3,5-9 and 12-23 is/are pending in the application.
- 4a) Of the above claim(s) 7-9, 17-18 is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1-3,5,6,12-16 and 19-23 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on _____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
 2. ☐ Certified copies of the priority documents have been received in Application No. _____.
 3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|--|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413) |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | Paper No(s)/Mail Date. _____ |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08) | 5) <input type="checkbox"/> Notice of Informal Patent Application |
| Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____ |

DETAILED ACTION

Continued Examination Under 37 CFR 1.114

1. A request for continued examination under 37 CFR 1.114, including the fee set forth in 37 CFR 1.17(e), was filed in this application after final rejection. Since this application is eligible for continued examination under 37 CFR 1.114, and the fee set forth in 37 CFR 1.17(e) has been timely paid, the finality of the previous Office action has been withdrawn pursuant to 37 CFR 1.114. Applicant's submission filed on 01/15/2009 has been entered.

Response to Amendment

2. Applicant's arguments filed on 01/15/2009 have been fully considered but they are not persuasive.

3. The applicant argues (see page 11) regarding the amended **claim 1** that Kim does not disclose the dummy line is on the insulating layer. The examiner respectfully disagrees. **Kim et al.** teaches the ground wiring being formed into two layers, one is under the insulating layer and another one is above the insulating layer (see at least paragraph 39; 700, figure 6). In fact, **Kim et al.** (in at least paragraph 22, figures 1, 3-4, 6) teaches the insulating film covers the plurality of line-on glass type signal lines and the dummy line (700) is formed on the layer of the insulating film (640). Therefore, it would have been obvious to one of ordinary skill in the art at the time of the invention to combine the insulating film as taught by **Kim et al.** because such modification would reduce the EMI effect and the wireless frequency interference.

4. Applicant's arguments with respect to **claims 1-3, 5-6, 12-16, 19-23** have been considered but are moot in view of the new ground(s) of rejection.

Art Unit: 2871

Claim Rejections - 35 USC § 103

5. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

6. **Claims 1-3, 5-6, 12-16, 21** are rejected under 35 U.S.C. 103(a) as being unpatentable over **Kawaguchi (US 6,052,171)** in view of **Kim et al. (KR 10-1999-0024956)**.

7. Regarding **claim 1, Kawaguchi** (figure 1A) discloses a line-on glass liquid crystal display panel, comprising:

- a picture display part having liquid crystal cells at each intersection of gate lines and data lines (see at least column 4, lines 10-20);
- **Kawaguchi** (figure 1A) implicitly discloses data pads extended from file data lines in an outer area of the picture display part; gate pads extended from the gate lines in the outer area of the picture display part; a plurality of line-on glass signal pads formed just beside an end of the gate pads; the first and second line-on glass signal pads being in one corner of the outer area of the picture display part;
- a plurality of line-on glass type signal lines (13; see at least column 6, lines 60-65) connecting the first and second line-on glass signal pads in the corner of the outer area of the picture display part for applying gate power voltage signals and gate control signals to gate drive ICs in order to drive gate signal lines of the picture display part; and

Art Unit: 2871

- **Kawaguchi** (figure 1A) implicitly discloses a plurality of first dummy pads between the first line-on glass type signal pads and a plurality of second dummy pads between the second line-on glass type signal pads; and
- a plurality of dummy lines (12) connecting the first and second dummy pads in the one corner of the outer area of the picture display part, wherein the plurality of dummy lines are formed between the line-on glass type signal lines for applying a common voltage as a reference voltage to drive the liquid crystal cells,

8. **Kawaguchi** is silent regarding forming the insulating layer. **Kim et al.** (in at least paragraph 22, figures 1, 3-4, 6) teaches the insulating film covers the plurality of line-on glass type signal lines and the dummy line (700) is formed on the layer of the insulating film (640).

Therefore, it would have been obvious to one of ordinary skill in the art at the time of the invention to combine the insulating film as taught by **Kim et al.** because such modification would reduce the EMI effect and the wireless frequency interference.

9. Regarding **claim 2**, **Kawaguchi** (figure 1A) implicitly discloses the first and second line-on glass signal pads which extend from both sides of the line-on glass type signal lines and are respectively formed between the end of the gate pads and the end of the data pads.

10. Regarding **claim 3**, **Kawaguchi** (figure 1A) implicitly discloses first and a second dummy pads that extend from both sides of the dummy line between the gate pads and the data pads (150 and 124).

11. Regarding **claim 5**, **Kim et al.** (figures 1, 3-4, 6) discloses the line-on glass type signal lines (620) are formed in a same layer as the gate line (621) of the picture display part.

Art Unit: 2871

12. Regarding **claim 6, Kim et al.** (figures 1, 3-4, 6) discloses the dummy line (700) is formed in a same layer as a data line (621, figure 4) of the picture display part with a gate insulating film therebetween (640).

13. Regarding **claim 12, Kawaguchi** (figure 1A) discloses a fabricating method of a line-on glass liquid crystal display panel, comprising:

- forming gate lines in a picture display part and a plurality of line-on glass signal lines (13; see at least column 6, lines 60-65) in one corner of an outer area of the picture display part on a substrate for applying gate power voltage signals and gate control signals to gate drive ICs in order to drive gate signal lines of the picture display part (see at least column 4, lines 30-35);
- forming data lines (11) to cross the gate lines in a picture display part and a dummy line (12) that is located between the line-on glass signal lines for applying a common voltage as a reference voltage; and
- **Kawaguchi** (figure 1A) implicitly discloses forming data pads extended from the data lines and gate pads extended from the gate lines in the outer area of the picture display part and forming first and second line-on glass signal pads just beside the data pads and gate pads, respectively, and first dummy pads between the first line-on glass signal pads and second dummy pads between the second line-on glass pads, respectively, in one corner of the outer area of the picture display part;
- wherein each of the plurality of the line-on glass signal lines is connected between the first and the second line-on glass signal pads in the one corner of the outer area of the picture display part.

Art Unit: 2871

14. **Kawaguchi** is silent regarding forming the insulating layer. **Kim et al.** (in at least paragraph 22, figures 1, 3-4, 6) teaches forming at least one layer of insulating film (640) to cover the line-on glass type signal lines (620 or 621) and the dummy line (700) is formed on the layer of the insulating film (see at least paragraph 0039). Therefore, it would have been obvious to one of ordinary skill in the art at the time of the invention to combine the insulating film as taught by **Kim et al.** because such modification would reduce the EMI effect and the wireless frequency interference.

15. Regarding **claim 13**, **Kim et al.** (figures 1, 3-4, 6) discloses forming a gate electrode connected to the gate line of the picture display part on the substrate; forming a gate insulating film (660) on the substrate on which the gate line and the gate electrode are formed; forming a semiconductor layer on the gate insulating film; forming a source electrode connected to the data line, and a drain electrode opposite to the source electrode with a designated gap therebetween (630), on the substrate on which the semiconductor is formed; forming a protective film (640) on the substrate where the data line, the source electrode and the drain electrode are formed; and forming a pixel electrode (650) connected to the drain electrode on the protective film.

16. Regarding **claim 14**, **Kim et al.** (figures 1, 3-4, 6) discloses the line-on glass signal line is formed of a same metal as a gate line (62').

17. Regarding **claim 15**, **Kim et al.** (figures 1, 3-4, 6) discloses the dummy line is formed of a same metal as the data line (700 and 621).

18. Regarding **claim 16**, **Kim et al.** (figures 1, 3-4, 6) discloses the dummy line (700) is formed between the line-on glass type signal lines (620) with the gate insulating film therebetween (640).

Art Unit: 2871

19. Regarding **claim 21, Kawaguchi** (figure 1A) discloses a line-on glass liquid crystal display panel, comprising:

- a picture display part with a matrix of liquid crystal cells having a plurality of gate lines and data lines to cross each other (see at least column 4, lines 10-20)
- **Kawaguchi** (figure 1A) implicitly discloses a gate pad and a data pad to drive the gate lines and data lines, respectively;
- a plurality of line-on glass type signal lines (13; see at least column 6, lines 60-65) located in one corner of an outer area of the picture display part of a lower substrate for applying drive signals to drive the liquid crystal cells, wherein the one corner is between the gate pad and the data pad;
- a plurality of dummy lines (12) that formed between the line-on glass type signal line;
- and the plurality of dummy lines are a common voltage line or a ground voltage line.

20. **Kawaguchi** is silent regarding forming the insulating layer. **Kim et al.** (in at least paragraph 22, figures 1, 3-4, 6) teaches forming an insulating film (640) to cover the line-on glass type signal lines (620 or 621) and the dummy lines (700) being formed on the layer of the insulating film (see at least paragraph 0039); wherein the dummy lines and the data lines are on the insulating layer. Therefore, it would have been obvious to one of ordinary skill in the art at the time of the invention to combine the insulating film as taught by **Kim et al.** because such modification would reduce the EMI effect and the wireless frequency interference.

21. **Claims 19-20 and 22-23** are rejected under 35 U.S.C. 103(a) as being unpatentable over **Kawaguchi** in view of Kim; further in view of **Song et al. (US 2002/0008794)**.

Art Unit: 2871

22. Regarding **claim 19, Kawaguchi** (figure 1A) discloses a line-on glass liquid crystal display panel, comprising:

- a picture display part with a matrix of liquid crystal cells having a plurality of gate lines and data lines to cross each other (see at least column 4, lines 10-20)
- **Kawaguchi** (figure 1A) implicitly discloses a gate pad and a data pad to drive the gate lines and data lines, respectively;
- a plurality of line-on glass type signal lines (13; see at least column 6, lines 60-65) located in one corner of an outer area of the picture display part of a lower substrate for applying drive signals to drive the liquid crystal cells, wherein the one corner of the outer area of the picture display part is corresponding to between the gate pad and the data pad;
- a plurality of common voltage signal lines (12) for applying a common voltage signal and being formed between the line-on glass lines,
- wherein at least one of the plurality of common voltage lines applies the common voltage signal through a silver(Ag) dot to a common electrode that is formed on an entire surface of an upper substrate (14).

23. **Kawaguchi** is silent regarding forming the insulating layer and the silver dot. **Kim et al.** (in at least paragraph 22, figures 1, 3-4, 6) teaches forming an insulating film (640) to cover the line-on glass type signal lines (620 or 621) and common voltage signal lines (700) being formed on the layer of the insulating film (see at least paragraph 0039). Therefore, it would have been obvious to one of ordinary skill in the art at the time of the invention to combine the insulating film as taught by **Kim et al.** because such modification would reduce the EMI effect and the wireless frequency interference.

Art Unit: 2871

24. In addition, **Song et al.** (in at least paragraph 0014, figure 4) teaches at least one of the plurality of common voltage lines applies the common voltage signal through a silver(Ag) dot (63) to a common electrode that is formed on an entire surface of an upper substrate. Therefore, it would have been obvious to one of ordinary skill in the art at the time of the invention to combine the silver dot as taught by **Song et al.** because such modification would provide an electrical connection with the common electrode of the upper substrate.

25. Regarding **claim 20**, **Kawaguchi** (figure 1A) discloses the line-on glass liquid crystal display panel according to claim 19, wherein the gate signal lines are Vgl, Vcc, Vgh, GOE, GSC, OSP.

26. Regarding **claim 22**, **Kawaguchi** (figure 1A) discloses the gate signal lines are Vgl, Vet, Vgh, GOE, GSC, GSP.

27. Regarding **claim 23**, **Kawaguchi** is silent regarding forming the silver dot. **Song et al.** (in at least paragraph 0014, figure 4) teaches at least one of the plurality of common voltage lines applies the common voltage signal through a silver(Ag) dot (63) to a common electrode that is formed on an entire surface of an upper substrate. Therefore, it would have been obvious to one of ordinary skill in the art at the time of the invention to combine the silver dot as taught by **Song et al.** because such modification would provide an electrical connection with the common electrode of the upper substrate.

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Lauren Nguyen whose telephone number is (571) 270-1428. The examiner can normally be reached on M-Th, 7:30-6:00 EST.

Art Unit: 2871

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, David Nelms can be reached on (571) 272-1787. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/L. N./

Examiner, Art Unit 2871

/Andrew Schechter/

Primary Examiner, Art Unit 2871